

Product Specifications

Model: MCC-070 Platform

Charge Cables

- 2m (Standard)
- 3m
- 5m

Power Cord

Accepts locking C13 connector for region-specific power cables:

- United States: EMA 5-15 termination, rated at 15A/125V UL CSA
- EU & Latin America: 10A/250V IEC60320 / VDE
- Japan: PSE 15A/125V

Applications

- Automotive
- Heavy-Duty
- Power Sports
- Marine
- Group 31
- Commercial 4D/8D

Battery Chemistries

- Lead acid
- AGM
- EFB
- Lithium ion

Rating System

- CCA
- CA
- MCA
- JIS
- DIN
- SAE
- IEC
- EN

Operating Parameters

- Input Voltage: 120 VAC; 60 Hz; 12A maximum, 240 VAC, 50 Hz, 10A maximum
- Output: 15VDC; 70A maximum

Temperature

- Operating temperature range: 0°C to +60°C (32°F to +140°F)
- Storage temperature range: -10°C to +85°C (14°F to 185°F)

Dimensions

- (without handle or base)
- Height: 4.80 in (12.19 cm)
 - Width: 13.1 in (33.27 cm)
 - Length: 12.0 in (30.48 cm)
 - Weight: 18 lbs

Humidity

15% to 85% R.H., non-condensing

Certifications

- CUL
- RoHS
- TUV
- CEC
- FCC

Connectivity

- Wi-Fi
 - 802.11 b/g/n 2.4GHz
 - Security – WEP, WP, WPA-2 Enterprise

Bluetooth

- 2.0
- USB 2.0 connection
- BTLE

CAN bus interface

Safety Features

- Reverse polarity
- Clamp connection
- Non-12V battery connection
- Battery voltage too low (< 5.5 V)
- Clamp high temperature detection

BMIS-Enabled

- Remote "over the air" software updates
- Remote diagnostics
- Enterprise asset management
- Reporting and analytic tools
- Communication with next generation Midtronics platforms and tools

User Interface

- Advanced navigation and charge applications
- Remote notifications (Wi-Fi- or Bluetooth-enabled)
- Intuitive charge cycle feedback
- 3.5" color display
- 5-button keypad

Corporate Headquarters

Willowbrook, IL USA
Phone: 1.630.323.2800
Toll Free in US: 1.800.776.1995
Toll-Free in Canada: 1.866.592-8053

European Sales

Midtronics b.v.
European Headquarters
Houten, The Netherlands
Serving Europe, Africa, the Middle East,
and The Netherlands
Phone: +31 306 868 150

Midtronics China Office

China Operations
Shenzhen, China
Phone: +86 755 8202 2036

Asia/Pacific (excluding China)

Contact Corporate Headquarters
Phone: +1.630.323.2800

Midtronics India

Mumbai, India
Phone: +91.989 237 6661

MIDTRONICS

www.midtronics.com @midtronics

190-000114A ©2016 Midtronics

MIDTRONICS

Advancing
Battery Management

MCC-070

Economical,
Easy-to-use
Charging Solution

MCC-070 CONTROLLED CHARGER

Part of an Advanced Battery Management Solution

The Midtronics MCC Controlled Charger offers an easy-to-use, economical solution to vehicle charging service.

As the controlled charging component of the Midtronics Advanced Battery Management solution, the MCC's connected functionality enables advanced features designed to improve operational efficiency and enhance its value to your organization.

Dealership Service Garages

- Pre-Delivery Inspection – Vehicle to Dealer
- Pre-Delivery Inspection – Vehicle to Customer
- Lot inventory maintenance
- Service visits
- ECU reflash of onboard computers

Aftermarket & Retail Service Garages

- Walk-in
- Service visit
- Stock management

- Economical charging solution that doesn't require techs to be battery or charger experts
- Pre-programmed applications tailored to your battery management program
- Streamlined, easy-to-use interface simplifies charging applications
- Offers reflash support, quick fill, and full charging capabilities
- Also functional as a standalone product

Several key capabilities uniquely position the MCC as an ideal charging solution for today's vehicles, shops, and technicians



App-based Charging

- User can focus on what actions need to be performed on the vehicle, rather than having to know or learn what specific kind of charging needs to be done
- Process-driven applications help users get more consistent and accurate results

Enhanced User Interface

- Purpose-designed for optimal user experience
- Easy-to-read, clean & simple text
- Easy to learn and use, minimal training required
 - Streamlined, logical system navigation & button design for faster, more efficient service routines
 - Adaptable design for multiple user skill and experience levels
 - Colorful function icons to provide an intuitive user interface



Special Algorithms with Switch-Mode Power

- Provide controlled and safe charging to quickly service different battery types (regular lead-acid, AGM, EFB)
- Future provision for Li-Ion service

Protected Output

Circuit breaker prevents unsafe failures that may short the positive post of the battery to the chassis (ground) of the vehicle.

Seamless Integration with BMIS and Midtronics Diagnostic Tools

The MCC offers seamless integration with Midtronics diagnostic tools and BMIS in an advanced battery management solution, as well as benefits to address the unique needs of any service application:

- Charges batteries – including new AGM & EFB models – effectively and quickly
- Safe & easy to use
- Clearly indicates charger status: charging, charge complete, charging error/fault
- Automatic and efficient charge recovery for deeply discharged batteries
- Manual voltage & current limit selections
- Temperature-based selectable charging limits
- Provides on demand current and constant clean voltage to the vehicle battery for the extended period of time required to update the vehicle computer software
- Selectable voltage levels from 11 – 16 VDC

Wireless Communication & Network Capability

- Remote monitoring of charge cycle status throughout the entire shop/store with the DSS or 3rd party smart devices
- Seamless integration with Midtronics equipment and data system in an advanced battery management solution
- Integrated charging process
 - Improves speed and tracking capabilities
 - Midtronics DSS Battery Diagnostic Service System platform transmits vehicle battery information to the MCC
 - MCC final charging data (voltage, Ah, current, etc.) available to DSS and the Midtronics Battery Management Information System (BMIS)

Battery Management System Technology

DSS-7000

Battery Diagnostic Service System



MCC-070

Controlled Charger Communicates with DSS-7000



Cloud-Based Data

- Wireless equipment software updates
- Cloud storage of diagnostic service, location, vehicle & team activity data
- Robust analytical tools
- Flexible, comprehensive reporting options

Gateway Router

Communicates with paired devices



CVG-3

Identifies vehicles through OBD-II port for automatic testing

