



DIAGNOSTICS, RE-PROGRAMMING, ABS BRAKE BLEEDING

BSU2-50B provides a stable voltage and up to 50 amps of fully regulated power to prevent loss of charge and damage to the battery.

BSU2-50B can be used with any 12V automotive battery including AGM and GEL.

When the battery is charged the BSU is a regulated power supply to sustain accessory loads and offset parasitic drain.

Designed for use in the workshop and compatible with most diagnostic trolleys.

Reverse polarity protection.

Output current display.

Supplied with IEC power lead and 5m output leads as standard.

FEATURES

BSU2-50B

12V 50A

BATTERY SUPPORT UNIT

This low profile (3.5") **BSU2-50B** battery support unit provides a constant voltage to prevent loss of data and possible damage to control units during software updates, and module reprogramming as well as diagnostic processes when in a Key On, Engine Off state.

During diagnostic or programming operations, the vehicle's systems are operating solely from the battery. Maintaining battery charge during this process is critical.

Designed to be wall, ramp or trolley mounted the **BSU2-50B** has been designed to meet the needs of the high power consuming vehicle.



SPECIFICATIONS

INPUT

100-240v AC
50/60HZ

SIZE

280 x 190 x 90MM

OUTPUT

13.4v UP TO 50A
CONTINUOUS

CARTON

320x 250 x 230MM

WEIGHT

6KG

MANUFACTURING

UK

TRACTION CHARGER,
ROUNDWAY HILL
BUSINESS CENTRE,
DEVIZES,
WILTSHIRE
SN10 2LT

+44(0)330 022 7822
SALES@TRACTIONCHARGER.COM
TRACTIONCHARGER.COM