



DIAGNOSTICS, RE-PROGRAMMING, ABS BRAKE BLEEDING

BSU2-125/B-US provides a stable voltage and up to 90 amps of fully regulated power to prevent loss of charge and damage to the battery.

BSU2-125/B-US can be used with any 12V automotive battery including AGM and GEL.

When the battery is charged the BSU is a regulated power supply to sustain accessory loads and offset parasitic drain.

Designed for use in the workshop and compatible with most diagnostic trolleys.

Reverse polarity protection.

Output current display.

Supplied with IEC power lead and 5M output leads.

FEATURES

BSU2-125/B-US
90A

BSU2-125/B-US provides a constant voltage to prevent loss of data and possible damage to control units during software updates, and module reprogramming as well as diagnostic processes when in a Key On, Engine Off state.

During diagnostic or programming operations, the vehicle's systems are operating solely from the battery. Maintaining battery charge during this process is critical.

The status of **BSU2-125/B-US** is indicated simply by three LED's – POWER, POLARITY, DEMAND. When all 3 are illuminated, **BSU2-125/B-US** is supporting the battery.

Designed to be wall, ramp or trolley mounted the **BSU2-125/B-US** has been designed to meet the needs of the high power consuming vehicle.

Approved by Jaguar and Landrover.

BATTERY SUPPORT UNIT

SPECIFICATIONS

INPUT

90-260VAC

OUTPUT

≈ 13.4V UP TO 90A

CONTINUOUS

WEIGHT

8KG

SIZE

295 x 255 x 130MM

MANUFACTURING ORIGIN

UK



TRACTION CHARGER,
ROUNDWAY HILL
BUSINESS CENTRE,
DEVIZES,
WILTSHIRE
SN10 2LT

+44(0)330 022 7822
SALES@TRACTIONCHARGER.COM
TRACTIONCHARGER.COM