

FOLDING ROOFS, HIGH POWER HIFI, AUTO TAILGATE DEMOS, SOTWARE DOWNLOADS, **WORKSHOP MAINTENANCE**

CSU2-50B provides a stable voltage and up to 50 amps of fully regulated power to prevent loss of charge and damage to the battery.

CSU2-50B can be used with any 12V automotive battery including AGM, GEL and LiFeP04.

In SSU mode, when the battery is charged the CSU is a regulated power supply to sustain accessory loads and

offset parasitic drain with battery state detection, ensuring safe prolonged use.

In BSU mode a continuous power source is supplied to the battery until physically removed.

Output current display.

Reverse polarity protection.

Disconnect detection.

Supplied with IEC power lead and 3M output leads.

FEATURES

CSU2-50B

50A

This low profile (90mm) CSU2-50B has been designed specifically for car showrooms and workshops.

Most conventional battery conditioners simply trickle charge the battery after it has been drained. The CSU2-50B provides instant support to the battery negating the need for recharging.

With the CSU2-50B support unit connected to your vehicles you can be sure that they are always ready for demonstration and downloads and that the battery will be kept in prime condition.

This unit has been designed to slip under most vehicles without scratching the floor surface and features automatic current

sensing in SSU mode so that it knows when it is needed. It can also be trolley mounted for workshop applications.

The intelligent sensing in the CSU2-50B determines exactly when support is required to minimize unnecessary noise and power consumption.



SPECIFICATIONS

INPIIT

100-240 VAC 50/60HZ

SIZE

280 x 190 x 90mm

OUTPUT

WEIGHT

6KG

13.4v IIP TO 50A **CONTINUOUS**

CARTON

400 x 400 x 200mm

MANUFACTURING ORIGIN

UK

TRACTION CHARGER. **ROUNDWAY HILL BUSINESS CENTRE.** DEVIZES. WILTSHIRE **SN102LT**

+44 (0) 330 022 7822 SALES@TRACTIONCHARGER.COM TRACTIONCHARGER.COM