



FOLDING ROOFS, HIGH POWER HIFI, AUTO TAILGATE DEMOS

SSU2-50B provides a stable voltage and up to 50 amps of fully regulated power to prevent loss of charge and damage to the battery.

SSU2-50B can be used with any 12V automotive battery including AGM and GEL.

When the battery is charged the SSU is a regulated power supply to sustain accessory loads and offset parasitic drain.

Battery state detection, ensuring safe prolonged use.

Output current display.

Reverse polarity protection.

Disconnect detection.

Supplied with 5M IEC power lead and 3M output leads.

FEATURES

SSU2

50A

SHOWROOM SUPPORT UNIT

This low profile (90mm) battery conditioner has been designed specifically for car showrooms.

Most conventional battery conditioners simply trickle charge the battery after it has been drained. The **SSU2-50B** provides instant support to the battery negating the need for recharging.

With the **SSU2-50B** showroom conditioner connected to your vehicles you can be sure that they are always ready for demonstration and that the battery will be kept in prime condition.

This unit has been designed to slip under most vehicles without scratching the floor surface and features automatic current

sensing so that it knows when it is needed.

The intelligent sensing in the **SSU2-50B** determines exactly when support is required to minimize unnecessary noise and power consumption.



SPECIFICATIONS

INPUT

100-240VAC

50/60Hz

SIZE

280 x 190 x 90MM

CARTON

320 x 250 x 230MM

OUTPUT

13.4v UP TO 50A

CONTINUOUS

FORMAT

**AVAILABLE IN UK, EU, AU AND US
MAINS INPUT LEAD VARIANTS**

WEIGHT

6KG

MANUFACTURING ORIGIN

UK

**TRACTION CHARGER,
ROUNDWAY HILL
BUSINESS CENTRE,
DEVIZES,
WILTSHIRE
SN10 2LT**

**+44(0)330 022 7822
SALES@TRACTIONCHARGER.COM
TRACTIONCHARGER.COM**